

MARCH NEWS

In this issue:

- MACal 8900PRO Gold & Silver now in stock
- POLI-FLEX TURBO 4900 Series (White, Black & Red) - **SPECIAL**

MACmark - MACAl 8900 Pro

A unique intermediate film with up to 3-4 years outdoor life, featuring a unique removable, solvent based, acrylic adhesive. **Excellent removability.**

Colours available: Gold (MACAl 8979-00) & Silver (MACAl 8969-00)



POLI-FLEX TURBO—**SPECIAL THIS MONTH**

Newest polyurethane transfer film equipped with a special hotmelt for fast application **at low temperature.**

Suitable for transfer to textiles like cotton, polyester, uncoated nylon, mixtures of polyester/cotton and polyester/ acrylic. For application to Nylon that is treated with any kind of coating, please test for suitability. POLI-FLEX® TURBO can be used for lettering on T-shirts, sport & leisure wear, sport bags and promotional articles.

Transfer Conditions

Pressure: 2,5 - 3,0 bar [medium pressure]

Temperature / Time: 130 °C, 5 sec. / 150 °C, 4 sec. / 160 °C, 3 sec. NYLON

Pressure: 2,0 bar [low pressure]

Temperature / Time: 150 °C,

- Pre Heat 5 sec.
- Apply to Nylon 5 sec.
- Remove PET liner, cover transfer with silicon paper & apply for further 10 sec.

Please consider to adjust the application time when using highly structured cotton or cotton mixture fabrics.

GIVE US A CALL FOR PRICING

	Cotton	Cotton / Polyester (Mixture)	Impregnated Textiles (Nylon etc.)
POLI-FLEX TURBO	130°C, 5 sec. 150°C, 4 sec. 160°C, 3 sec. 2,5 - 3,0 bar [medium pressure]	130°C, 5 sec. 150°C, 4 sec. 160°C, 3 sec. 2,5 - 3,0 bar [medium pressure]	150°C • Pre Heat 5 sec. • Apply to Nylon 5 sec. • Remove PET liner, cover transfer with silicon paper & apply for further 10 sec. 2,0 bar [low pressure]