

# Monstrous adhesion – MonsterTack ASLAN DFP 05

## MonsterTack ASLAN DFP 05 sticks, lasts, and does exactly what it promises:

This polymeric, glossy digital printing film with its amazing new adhesive formulation, which is highly resistant to solvent vapors and lubricating oil, offers assurance for your most challenging applications.

And yes, we mean really challenging: motocross vehicles for instance, helmets, sports armour, campers and mobile homes. Decals on construction vehicles, agricultural and industrial machines, that are subject to extreme mechanical stress and heavy pollution. Signage on box trailer (those often come with a dirt repellent surface) and caravans. Other demanding applications include gas pumps, low-energy surfaces and ABS plastics – often used for household items and electrical appliances. In fact, wherever extreme conditions prevail.

In addition, this special adhesive system offers so much more. Despite its extremely high adhesive strength, the **MonsterTack ASLAN DFP 05** can be removed clean from low-energy surfaces and steel, leaving no film or adhesive residues. It can also be applied at low temperatures from 14° F and therefore offers versatility and security in one.



## Your advantages of MonsterTack ASLAN DFP 05 at a glance:

- bonding temperature from 14° F
- monstrous adhesion for the most difficult applications on box trailers, powder coated surfaces, gas pumps, snow mobiles, moto cross bikes, helmets, sports armor... etc.
- resistant to solvent vapors and lubricating oil
- clean removal from low-energy surfaces & steel
- solvent-free adhesive
- no edge bleeding adhesive
- classified to salt spray test ISO 9227:2017

## Want to know more?

Order your samples:  
[www.aslanvinyls.com](http://www.aslanvinyls.com)



**ASLAN®**

EXPERTISE IN SELF-ADHESIVE FILMS





#### MonsterTack ASLAN DFP 05

Thickness	2.8 mil	
Durability	up to 7 years	
Printability	Solvent-, eco-solvent-, latex-, UV curable inks, screen printing	
Film	PVC, polymeric	
Surface	white glossy	
Dimensions	48" x 50 yds	
Temperature	bonding temperature from 14° F	
Adhesive strength (ASTM D903) after 72 hours:	~ 34 N/25mm (steel) ~ 30 N/25mm (PE)	~ 28 N/25mm (PP) ~ 32 N/25mm (PMMA)

**US sales and distribution center**  
**POLI-TAPE USA Inc.**  
 8100-2 Westside Industrial Dr  
 Jacksonville, FL 32219  
 United States of America

**Head office and manufacturing**  
**ASLAN Selbstklebefolien GmbH**  
 Oberauel 2 | 51491 Overath  
 Germany  
**phone** +49 2204 708-80

**Please contact us**  
**phone** (904) 215-1411  
**email** [info@aslanvinyls.com](mailto:info@aslanvinyls.com)  
**web** [www.aslanvinyls.com](http://www.aslanvinyls.com)



ASLAN – A POLI-TAPE  
 Group Company

**ASLAN**<sup>®</sup>  
 EXPERTISE IN SELF-ADHESIVE FILMS