

Carrflex® Blockout 440gsm**Description**

Lightweight coated USB (Ultra Smooth Blockout) with fire retardant (B1 standard), printable both sides. Ideal for a range of indoor applications. Also popular for pull up banners.

Specifications/Features

Weight	440gsm
Base Fabric	Woven Polyester (High Tenacity, Low Shrinkage)
Yarn Thickness	250 D x 250 D
Thread Count	36 x 36 (per inch)
Coating	PVC coated front and back
Fire Retardant	Produced to B1 (DIN 4102-B1) Tested to AS/NZS 1530 Part II & III
Tensile Strength	Warp – 1,300 N/5cm Weft – 1,000 N/5cm
Tearing Strength	Warp – 45 N/5cm Weft – 40 N/5cm
Coating Adhesion	60 N/5cm
Special Treatment	UV Stabilised
Fabrication Method	Hot Air, Hot Wedge, High Frequency Welding, Stitching
Applications	Indoor Banners (Single and double sided print), Pull Up Banners

Ink Compatibility**Accreditation**

Information on physical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and not for use in specifications. They are intended only as a source of information and given without guarantee and do not constitute a warranty. Purchasers should independently determine prior to use, the suitability of any material for their specific use.

CARR NEW ZEALAND LIMITED

Tel: 64 9 274 0869
6 Ra Ora Drive, East Tamaki, Auckland 2013, New Zealand
PO Box 204110, Highbrook, Auckland 2161, New Zealand
info@carrgroup.co.nz

CARR AUSTRALIA PTY LIMITED

Tel: 61 2 9636 9525
1 Spireton Place, Pendle Hill, NSW 2145, Australia
PO Box 335, Pendle Hill, NSW 2145, Australia
info@carrgroup.com.au